

Wireless Keyfob Panic

- Simple 3-step “learn-in” for 319.5 MHz, 345 and 433 MHz wireless control panels.
- Lightweight and compact:
2.37” L x 1.5” W x .4” D
- LED ring activates (red) when function button is pressed.
- Long-life battery—8 years, simple to replace.
- Built with MaxOut™ Technology for maximum Radio Frequency (RF) security sensor reliability. MaxOut high performance sensors deliver the maximum FCC allowable output for maximum signal strength and range.

Regulatory:

- FCC compliant.
- Canadian IC compliant

The RF-FOB-PANIC-NN is a wireless handheld device that is used as a life safety, emergency panic and help device.

The sensor is powered by a replaceable 3-VDC, Lithium coin-cell battery.

The RF-FOB-PANIC Features:

- Portable device for emergency or help signal to the control panel and central station.
- Compact design with a single button with comfortable feel. White ring on button turns red when pressed and signal sent.
- Strong, reliable RF signal to control panel.
- 8 year battery life.
- Includes neck lanyard.



Specifications

Model Number and Ordering:	RF-FOB-PANIC-319-NN RF-FOB-PANIC-345-NN
RF Frequency:	319.5 MHz 345 MHz
Compatibility:	319.5 MHz: UTC®, Interlogix®, GE®, and ITI® , and Qolsys® 345 MHz: Honeywell® and 2GIG®
Battery Type: (Requires 1)	3-VDC Lithium Coin-Cell Battery, Varta or Panasonic CR2032
Operating Temperature Range:	32 to 120°F (0 to 49°C)
Storage Temperature Range:	-30 to 140°F (-34 to 60°C)
Relative Humidity:	95% Non-Condensing
Dimensions (L x W x D):	2.37 in. x 1.5 in. x 0.40 in.

Regulatory

FCC: 2ABBZ-RF-FOB-PANIC-319
2ABBZ-RF-FOB-PANIC-345

IC: 11817A-RFFOBPANIC319
11817A-RFFOBPANIC345

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received,
including interference that may cause undesired operation.

This Class B digital apparatus complies with Canadian ICES-003.
Cet appareil numérique de la classe B est conforme à la norme
NMB-003 du Canada.