## **Wireless Water Sensor**

## • Patented antenna design\*.

- Maximizes signal transmission strength while minimizing battery energy draw-extending replacement time.
- Two battery design vs. one in competitive sensors. Delivers more than double battery life.
- Easy to install. Easy to "Learn" into:
  319.5 MHz control panels-UTC® Interlogix, GE®, and Qolsys®.
- 345 MHz–Honeywell® and 2GIG® control panels.
- Compact Size, attractive design, matt finish, and neutral color complement any décor.

Patents: \* U.S. Patent: 9,245,431 B2 Regulatory: FCC Rules, Part 15

Patented Antenna Design. Improved transmission efficiency, reduces battery energy draw.



High Tension Battery Holders. Protects against loss of available energy. Dramatically extends battery life.



Wherever the possibility of unwanted water exists in a home or business—the Water Sensor is the ideal "peace of mind" sensor to add to your security and life safety system.

If the possibility of water / toilet overflow, hose leak, sump pump failure, or pipe leak—the Water Sensor is on guard to alert of water accumulation and damage. Water is detected when water rises above contacts. Checks for water every 5 seconds and requires two positive checks for a valid alarm—reduces false alarms.

Suggested placement areas include;

- Near Water Heater.
- Near Washing Machines Water Hoses.
- Under Sinks.



MaxΟι

## Specifications

	Model Number:	C-RF-WATER-319-NN	
	RF Frequency:	319 MHz	
		345 MHz	
	Compatibility:	319 MHz	UTC®, Interlogixe,GEe, ITIe, and Qolsyse
		345 MHz	Honeywelle and 2GIGe
	Battery Type: (Requires 2)	2-VDC Lithium Coin-Cell Battery, Varta or Panasonic CR2032	
	Battery Life:	>5 years	
	Operating Temperature Range:	32 to 120°F (0 to 49°C) -30 to 140°F (-34 to 60°C) 95% Non-Condensing	
	Storage Temperature Range:		
	Relative Humidity:		
	Dimensions (L x W x D):	Sensor:	1.77" L x .7" W x .38" D
		Transformer:	2.5" L x 1" W x .5" D
Regulatory		<ul> <li>This device complies with part 15 of the FCC Rules.</li> <li>Operation is subject to the following two conditions: <ul> <li>(1) This device may not cause harmful interference, and</li> <li>(2) this device must accept any interference received,</li> <li>including interference that may cause undesired operation.</li> </ul> </li> </ul>	
		FCC ID: 2ABBZ-WIN-WATER-319: 2ABBZ-WIN-WATER-345	
		IC: 118	17A-RFWINWATER319
		118	17A-RFWINWATER345
		This Class B digital apparatus complies with Canadian ICES-003.	
		Cet appareil	numérique de la classe B est conforme à la norme NMB-

003 du Canada.

